



Lico Water Chiller Cassette Fan Coil

藏天花式風機盤管



型號			FP-68KM4-V	FP-102KM4-V	FP-136KM4-V	FP-170KM4-V	FP-204KM4-V	FP-238KM4-V
風量 Air Flow	H	CFM/CMH	400/680	600/1020	800/1360	1000/1700	1200/2040	1400/2380
	M		306/520	465/790	606/1030	759/1290	883/1500	1059/1800
	L		206/350	306/520	406/690	506/860	607/1032	706/1200
額定制冷量 Cooling Capacity		kW	3.7	5.6	7.1	9.1	11.0	12.6
額定制熱量 Heating Capacity		kW	5.6	8.4	11.2	13.9	16.7	19.5
水 流 量 Water Flow Rate		L/h	640	970	1260	1710	1920	2210
水 阻 Water Pressure Drop		kPa	11	18	19	17	19	22
水 容 量 Water Content		L	1.64	2.03	2.03	2.88	2.88	2.88
噪 音 Noise Level		dB(A)	41	45	46	47	50	52
輸 入 功 率 Fan Motor Power		W	62	96	132	152	189	220
運 行 電 流 Running Current		A	0.28	0.43	0.59	0.67	0.84	0.98
電 源 Power Supply		V/Ph/Hz	220V/1P/50Hz					
控 制 方 式 Operation Control		Wireless Controller / 無 線 搖 控						
機 身 尺 寸 Casing Dimensions (L x W x H)		mm	585x585x250	710x710x290		840x840x290		
面 板 尺 寸 Panel Dimension (L x W x H)		mm	680x680x30	830x830x30		980x980x30		
淨 重 Net Weight		kg	21.5	29		39		
管道尺寸 Pipe Size	In	in	ZG3/4"					
	Out	in	ZG3/4"					

1. 供冷工况參數: 進口空氣乾球溫度為27°C, 濕球溫度19.5°C, 進水溫度7°C, 回水溫度為12°C
2. 供熱工况參數: 進口空氣乾球溫度為20°C, 進水溫度60°C, 回水溫度為50°C

Nominal Cooling and Heating capacity are based on the conditions below:

- a) Cooling Entering Air Temp. : 27°C DB/ 19.5°C WB, Entering Water Temp. 7°C, Leaving Water Temp. 12°C
- b) Heating Entering Air Temp. : 20°C DB, Entering Water Temp. 60°C, Leaving Water Temp. 50°C